

ACOUSTIC SEALANT - For Gap Sealing Between Floorboards and Perimeters



Key Benefits

- Acoustic grade sealant
- Paintable
- Extra Large 380ml sized tube
- Intumescent so provides a 4 hour fire rating
- Ideal for use with many of our products
- Available from stock

Description

Our white Acoustic Sealant is a one-part fire retardant water-based acrylic sealant and an excellent sound blocker. It exhibits good adhesion to a wide variety of common building substrates without the need for a primer. Paintable with emulsion paints three hours after application. Allow 12 hours before over painting with gloss paints.

When subject to fire, the sealant will intumesce (expand and char), thus blocking the passage of fire and smoke.

Recommended for perimeter sealing of all floors and between the joints of square edged floorboards before installing any further sound insulation. This acoustic sealant makes the floor more airtight and so reducing sound leakage and contributing to the effectiveness of any additional sound insulation.

This versatile sealant can also be used for many other general purpose applications and can be used in a longer sized skeleton gun.

It is not recommended for use in external situations



Properties Values

Application temperature	+5°C to +40°C
Service temperature	-10°C to +70°C
Skinning time @ 20°C/65%RH	5 minutes
Cure rate	Time to full cure is dependent on sealant depth, ambient temperature and humidity.
Chemical resistance	Fair resistance to most alkalis and dilute acids; poor resistance to hydrocarbon solvents.
UV resistance	Not applicable
Service life	15 years +
Movement accommodation	Butt joints (movement in tension and compression): 10% Lap joints (movement in shear): 20%
Colours	White.

ADDITIONAL INFORMATION AND INSTALLATION DETAIL CAN BE FOUND ON OUR WEBSITE

Sound Service (Oxford) Ltd, Crawley Mill, Witney, OX29 9TJ Tel: 0845 363 7131 - Fax: 0845 363 7151
www.soundservice.co.uk

